



International Journal of Productivity and Performance Mana

Benchmarking masonry labor productivity Adnan Enshassi Sherif Mohamed Peter Mayer Karem Abed

Article information:

To cite this document:

Adnan Enshassi Sherif Mohamed Peter Mayer Karem Abed, (2007),"Benchmarking masonry labor productivity", International Journal of Productivity and Performance Management, Vol. 56 Iss 4 pp. 358 - 368

Permanent link to this document: http://dx.doi.org/10.1108/17410400710745342

Downloaded on: 22 September 2016, At: 04:14 (PT) References: this document contains references to 21 other documents. To copy this document: permissions@emeraldinsight.com The fulltext of this document has been downloaded 2994 times since 2007*

Users who downloaded this article also downloaded:

(2005),"Factors affecting construction labour productivity for Malaysian residential projects", Structural Survey, Vol. 23 Iss 1 pp. 42-54 http://dx.doi.org/10.1108/02630800510586907

(1995),"Measuring construction productivity: a practical approach", Work Study, Vol. 44 Iss 8 pp. 18-20 http://dx.doi.org/10.1108/00438029510103310

(2013),"Contractors perspective toward factors affecting labor productivity in building construction", Engineering, Construction and Architectural Management, Vol. 20 Iss 5 pp. 446-460 http://dx.doi.org/10.1108/ECAM-08-2011-0074

Technical University of Munich

Access to this document was granted through an Emerald subscription provided by emerald-srm:194764 []

For Authors

If you would like to write for this, or any other Emerald publication, then please use our Emerald for Authors service information about how to choose which publication to write for and submission guidelines are available for all. Please visit www.emeraldinsight.com/authors for more information.

About Emerald www.emeraldinsight.com

Emerald is a global publisher linking research and practice to the benefit of society. The company manages a portfolio of more than 290 journals and over 2,350 books and book series volumes, as well as providing an extensive range of online products and additional customer resources and services.

Emerald is both COUNTER 4 and TRANSFER compliant. The organization is a partner of the Committee on Publication Ethics (COPE) and also works with Portico and the LOCKSS initiative for digital archive preservation.

*Related content and download information correct at time of download.



The current issue and full text archive of this journal is available at www.emeraldinsight.com/1741-0401.htm

IJPPM 56,4

358

Received September 2006 Accepted December 2006

REFLECTIVE PRACTICE Benchmarking masonry labor productivity

Adnan Enshassi Civil Engineering Department, University of Gaza, Gaza City, Palestine Sherif Mohamed

Centre for Infrastructure Engineering, School of Engineering, Griffith University, Gold Coast, Australia

Peter Mayer Technische Universitaet Muenchen, Muenchen, Germany, and Karem Abed

Civil Engineering Department, University of Gaza, Gaza City, Palestine

Abstract

Purpose – Labor productivity is one of the most important factors that affect the physical progress of any construction project. In order to improve labor productivity, site production should be measured on a regular basis, and then compared to acceptable standard benchmarks. The objective of this paper is to measure masonry labor productivity in Gaza Strip, Palestine, using a consistent benchmarking approach.

Design/methodology/approach – Production data were collected from nine different construction projects located in Gaza. For each project, values for baseline productivity, disruption index, performance index and project management index were calculated.

Findings – Based on the nine targeted projects, the baseline productivity of masonry works in Gaza seems to range from 0.29 to 0.80 work-hours per square meter. Calculated values were utilized to develop a correlation between two project benchmarks (i.e. disruption and project management indices). AS only four out of the targeted nine projects performed reasonably well, the paper strongly recommends developing a benchmarking standard for each local construction firm in Palestine which may lead to an improvement in the national construction productivity.

Originality/value – The outcome of this research will improve the national construction productivity in Palestine and highlights the benefit of improving benchmarking standard.

Keywords Construction industry, Labor efficiency, Labour utilization, Benchmarking, Productivity rate, Palestine

Paper type Research paper

Introduction

In its simplest form, labor productivity could be defined as the hours of work divided by the units of work accomplished (Thomas, 1994). However, in reality, labor productivity is a much more complex phenomenon which largely depends on quite diverse factors such as site conditions, workers' competence, materials availability, weather, motivation, supervision, to name just a few. Management also affects labor productivity. Ganesan (1984), for example, reported that incompetent management of



International Journal of Productivity and Performance Management Vol. 56 No. 4, 2007 pp. 358-368 © Emerald Group Publishing Limited 1741-0401 DOI 10.1108/17410400710745342 the industry and its construction agencies, whether these are public or private, is a prime cause of low productivity. Often, labor productivity is a key factor contributing to the inability of many contracting organisations to achieve their project goals, which include, most importantly, the profit margin. Therefore, it is paramount to understand the main determinants of labor productivity, and to keep and compare accurate records of productivity levels across projects. This approach which is simply referred to as benchmarking has gained popularity in many production and service industries. Put simply, benchmarking is "a systematic and continuous measurement process".

In construction, however, benchmarking is not a straightforward task due to both the very nature of the industry which lacks solid data gathering and the remarkable fluctuation in productivity. Benchmarking attempts in construction are bound to face certain difficulties such as incomplete or non-existent data. Even if data are well recorded and retrievable, it would be highly dependent on the special characteristics of the project, e.g. size, type and budget. Therefore, it is difficult to use it effectively as a basis for comparison. The structure of the industry with its temporary nature in organizing the construction process, where a number of organizations get involved in designing and constructing a single project, adds to the complexity of the benchmarking task (Mohamed, 1996).

Benchmarking construction productivity

Over the years, construction productivity has been the focus of many reported research studies (Abdel-Razek and Hosny, 1990; Thomas and Sanders, 1991; Abdel-Razek, 1992; Hosny and Abdel-Razek, 1992; Abdel-Razek, 2004). Also many attempts have been made to model construction labor productivity (Adrian and Boyer, 1976; Adrian, 1987; Abdel-Razek and McCaffer, 1990; Thomas and Zavrski, 1999a, b; Abdel-Hamid *et al.*, 2004).

Researchers have a long tradition of measuring productivity at the industry or macro-economic level, typically making a longitudinal study of productivity trends, but this high-level analysis does not provide an indication of firm level performance (El-Mashaleh *et al.*, 2001). At the micro-level, however, there is a vast literature addressing productivity at the project or even activity level. Previous literature examined various influences on productivity through both longitudinal and cross-sectional studies among contemporaneous projects and/or activities. Man-hours employed and work produced get measured and compared to past records, or compared with other firms to obtain measurements of how efficient a firm is in undertaking its activities (Thomas and Napolitan, 1995; El-Mashaleh *et al.*, 2001).

The scope of most construction productivity research has been on partial measures, principally labor. While useful at the activity level, partial factor metrics are limited. In particular, they do not address complex interactions between different factors both within and across projects. Thomas and Napolitan (1995) proposed a (total) Factor Model to measure productivity at the activity level. They suggested that several influences on productivity (e.g., skill level, weather, site conditions, management, etc.) are separable and additive in nature. Their model, however, does not address interactions within and across projects and hence, is not applicable at the firm level. This lack of having a productivity measurement methodology for contractors, at the firm level, represents a serious gap in construction research that likely retards Benchmarking labor productivity industrial adoption of new methods. A productivity measure at the firm level has a host of benefits, as it supports (El-Mashaleh *et al.*, 2001):

- management decisions regarding resource utilization across projects to achieve highest return;
- management decisions about investment in resources and in mix of projects;
- benchmarking efforts, thus allowing contractors to better understand their competitive position and improve their performance; and
- · comparative research of various management policies.

In particular, a firm-level productivity measurement methodology allows empirical evaluation of improved management policies. For example, lean production tools such as the Last Planner and Shielding Production (Ballard and Howell, 1998) are productivity improvement techniques at the project and activity levels. While these techniques have proven useful, there is no methodology that could relate the activity and project level performance to the firms' performance (El-Mashaleh *et al.*, 2001).

Benchmarking construction labor productivity has become an important research topic at the global level. Thomas and Zavrski (1999b) developed a conceptual benchmarking model for international benchmarking of labor productivity for selected construction activities. Their model is widely applied in order to compare labor productivity in one construction project to that of another, and to establish the basis of benchmarking model developed by Thomas and Zavrski and builds upon the work of Abdel-Hamid *et al.* (2004), to measure, analyze and compare masonry labor productivity across nine different projects located in Gaza, Palestine.

Research methodology

The model of Thomas and Zavrski (known also as the theoretical model for international benchmarking of labor productivity) comprises two main steps:

- Determining project attributes which include collecting data pertaining to total work hours, total quantities, cumulative productivity, baseline productivity and number of abnormal days.
- (2) Calculating project performance parameters (benchmarks), these are: disruption index (DI), performance ratio (PR) and project management index (PMI).

Definitions and project attributes

- (1) Total work hours: summation of daily work hours in each project.
- (2) Total quantities: summation of daily quantities in each project.
- (3) Cumulative productivity: a measure of the overall effort required to finish the work.

Cumulative productivity $(hr/m^2) =$ Total work hours (hr)/Total quantities (m^2)

(4) Baseline productivity: the best performance a contractor can achieve for a particular design. It is calculated by applying the following steps to the daily productivity values for each project (Abdel-Hamid*et al.*, 2004; Thomas*et al.*, 2002):

IIPPM

56,4

360

- Determine the number of workdays that comprise 10 percent of the total workdays observed.
- Round this number to the next highest odd number; this number should not be less than five (5). This number, *n*, defines the size of (number of workdays in) the baseline subset.
- The contents of the baseline subset are the *n* workdays that have the highest daily production or output.
- · Calculate the sum of the work hours and quantities for these n workdays.
- The baseline productivity is the work hours divided by the quantities contained in the baseline subset.
- (5) Number of abnormal workdays: it follows that high variability in daily productivity is associated with poor labor performance. Thus, an important measure of performance is the number of abnormal or disrupted days. The range of random variability in daily productivity values when the project is satisfactorily managed is about twice the average baseline productivity of all projects (Abdel-Hamid *et al.*, 2004; Thomas and Zavrski, 1999a, b).

Project benchmarks DI, PR, PMI

• *Disruption index (DI)*: The first measure of labor performance (benchmarks) is the disruption index (DI). It is a measure of the daily productivity disruption within a single project. The following definition was selected as the simplest form (Abdel-Hamid *et al.*, 2004; Thomas and Zavrski, 1999a, b):

Disruption Index = Number of Abnormal (Disrupted) Work Days/ Total Number of Work Days

• *Performance ratio (PR)*: The performance ratio (PR) is the actual cumulative productivity divided by the expected baseline productivity (average values of baselines for all projects). Thus, the following definition was adopted (Abdel-Hamid *et al.*, 2004):

PR = Cumulative productivity/Expected Baseline productivity

• *Project management index (PMI)*: The PMI is a dimensionless parameter that reflects the contribution of project management to the cumulative labor performance on the project. The lower the PMI, the better was the project management's influence on overall performance (Abdel-Hamid *et al.*, 2004; Thomas and Zavrski, 1999a, b).

Project Management Index (PMI) = Cumulative Productivity – Baseline Productivity/ Expected Baseline productivity

Data collection

Data were collected from nine construction projects located in Gaza Strip in order to measure the labor productivity for masonry works. The targeted projects include residential buildings, schools governmental buildings, garage extension, and a university building. Table I shows the classification of the nine targeted projects. All projects data including crew size, daily work hours, and daily quantities (output) were

IJPPM 56,4	Project no.	Project name	Contractor	Project type	Total actual workdays
	1	Noor El Maaref School	Abed Al-Hakeem Ismael Co	School	18
362	2	Court House project	Moshtaha & Hassona Co.	Governmental building	114
502	3	Islamic Univ. building in southern area	Ata sons Co.	University	28
	4	Building for General Personnel	Hettawi Co.	Residential building	83
	5	Rehabilitation of packing houses in Goosh Kateef ex-settlement	Saqa & Khodari	Rehabilitation	16
	6	Ministry of Justice	Jehan Co.	Governmental	22
Table I	7	Al Amani building in Tal El hawa	Abu Shmala Co.	Residential	17
Classification and	8	Al Zitoun school	Al Zitoun Co Middle Fast Co	School Car parking	14
projects	J	parking	muule East Co.	complex	17

collected from the daily progress report sheet. Table II shows typical data collected for project number 1, The Noor El Maaref project.

Cumulative productivity = Total work-hours/ Total quantities = 590/1229 = 0.4801 whr/m²

Data analysis and discussion

Project attributes

To obtain the baseline productivity value for each project, daily labor productivity was calculated using the five steps previously listed. The highest productivity scores (no less than five scores) were considered to define the baseline subset, and the average of these figures represents the baseline productivity in the project. To demonstrate, for Project no. 1, the best scores of daily labor productivity (i.e. the lowest calculated figures) were found as 0.3772, 0.3730, 0.3970, 0.3439 and 0.4055 whr/m² and, therefore, the baseline productivity for this project equals to the average of these five figures which is 0.3793 whr/m², see Table II and Figure 1. The average baseline productivity, calculated for each project, divided by 9. The average baseline productivity is 0.4755 whr/m².

Any daily productivity that exceeds the figure (0.9510), which is twice the average baseline productivity for all nine projects (0.4755 * 2 = 0.9510 whr/m²), was considered abnormal. As such, all daily productivity values were compared to this figure in order to determine whether they are accepted or abnormal. The cumulative productivity of the nine projects ranged from 0.3453 whr/m² to 1.1782 whr/m². The cumulative productivity, in each project, is the total working hours in a certain project divided by the total quantities in the same project as shown in Table III.

Table III shows the total work hours, total quantities, cumulative productivity, baseline productivity and the abnormal workdays for each project. It could be seen that projects nos 2, 8 and 9 have the best baseline productivity figures, whereas project no. 3

Day	Crew size	Workhours (hr)	Daily qty (m ²)	Labor daily prod. (whr/m ²)	Baseline days	Benchmarking
1	2	16	27.53	0.5812		productivity
2	2	18	31.62	0.5693		productivity
3	4	36	95.44	0.3772	*	
4	6	48	128.7	0.3730	*	
5	5	45	94.31	0.4771		363
6	5	45	96.22	0.4677		000
7	6	48	120.92	0.3970	*	
8	5	40	116.31	0.3439	*	
9	5	44	79.56	0.5530		
10	5	40	71.31	0.5609		
11	4	32	78.92	0.4055	*	
12	4	36	51.91	0.6935		
13	5	40	60.2	0.6645		
14	4	32	46.02	0.6953		
15	2	16	34.96	0.4577		
16	3	24	46.4	0.5172		
17	2	16	28.79	0.5557		Table II.
18	2	14	19.89	0.7039		Data of Noor El Maaref
Sum		590	1,229.01	0.4801		project





has the worst baseline productivity which is 0.8012 whr/m^2 . This is not surprising as this particular project experienced a remarkably high number of abnormal (disrupted) days (18 out of 28 working days).

Project performance parameters (benchmarks)

Disruption index

As previously mentioned, the disruption index is the number of abnormal days divided by the number of the total working days, this value ranges from 0.0 to 1. The higher the

56,4	Project no.	Total workhour (hr)	Total qty. (m ²)	Total work days	Cumulative prod. (whr/m ²)	Baseline prod. (whr/m ²)	No of abnor. days
	1	590	1,229	18	0.4801	0.3793	0
	2	3,208	9,270	114	0.3461	0.3012	7
364	3	648	550	28	1.1782	0.8012	18
	4	1,997	4,153	83	0.4809	0.4332	14
	5	453	452	16	1.0022	0.711	8
	6	823	1,296	22	0.6350	0.4431	2
	7	690	983	17	0.7019	0.5882	3
Table III.	8	518	1,500	14	0.3453	0.291	0
Project attributes	9	543	1,370	17	0.3964	0.3312	1

DI, the more abnormal days the project experienced (i.e. poor project). The calculated disruption indices for the nine projects are presented in Table IV.

Examining the DI values listed in Table IV reveals that projects nos 1, 2, 8 and 9 have DI values of 0.0, 0.061, 0.00 and 0.059, respectively. These projects with such very small DI values (less than 0.1) were not disrupted projects. On the other hand, projects nos 3 and 5 have DI values of 0.643 and 0.5, respectively. These two projects were highly disrupted and had performed poorly.

Performance ratio (PR)

Table V shows the performance ratios of all nine projects, the lower the PR the better the project performance. It could be noticed that projects nos 2, 8 and 9 have the best performance ratios among the nine projects, with project no. 8 having the lowest ratio (best performance).

A number of projects performed poorly, most notably projects nos 3 and 5 with PR values of 2.48 and 2.11, respectively. These two projects have high PR values (PR >2.0) and also have high DI values (DI > 0.4). It is worth mentioning that the nature of the rehabilitation work in project no. 5 partially explains the relatively low productivity rates. Resource shortage was also experienced in project no 3. On the contrary, resource availability together with proper planning and follow-up procedures contributed to achieving the best baseline result in project no. 8. Generally speaking, the PR value

	Project no.	No of abnormal days	Total work days	Disruption index (DI)
	1	0	18	0.0000
	2	7	114	0.0614
	3	18	28	0.6429
	4	14	83	0.1687
	5	8	16	0.5000
	6	2	22	0.0909
	7	3	17	0.1765
Table IV.	8	0	14	0.0000
Disruption indices	9	1	17	0.0588

Project no.	Disruption index (DI)	Cumulative prod. (whr/m ²)	Performance ratio (PR)	Benchmarking labor
1	0.0000	0.4801	1.0096	productivity
2	0.0614	0.3461	0.7278	productivity
3	0.6429	1.1782	2.4778	
4	0.1687	0.4809	1.0113	
5	0.5000	1.0022	2.1077	365
6	0.0909	0.6350	1.3355	000
7	0.1765	0.7019	1.4762	Table V.
8	0.0000	0.3453	0.7263	Performance ratios and
9	0.0588	0.3964	0.8335	disruption indices

identifies the poorly performing project. It should be noted, however, that a PR value greater than 1.0 does not necessarily mean a poorly performing project, but rather is a comparison against the best overall performance observed in all projects. For example, projects nos 1, 4 and 6 have PR values greater than 1.0, but they have all performed reasonably well.

Project management index (PMI):

This index reflects the contribution of the project management to the cumulative labor performance on the project. The lower the PMI value, the better is the project management's influence on overall performance. PMI values for the nine projects are presented in Table VI. From Table VI, it could be concluded that projects nos 1, 2, 4, 7, 8 and 9 with PMI values less than 0.4 performed reasonably well. The same could not be said about projects nos 3 and 5 with PMI values 0.79 and 0.61, respectively.

Relationship between PMI and DI

Reviewing the PMI index and disruption index values reveals a strong relationship between the two indices. If the number of abnormal days increases in a certain project, the disruption index becomes larger and most often the reason behind such a case is poor project management. The results obtained for both indices support the correlation between the two indices. The worst PMI value (i.e. the highest value obtained) among all nine projects was obtained for project no 3, and is equal to 0.79. This was attributed

Project no.	Cumulative prod. (whr/m ²)	Baseline prod. (whr/m ²)	Project management index (PMI)	Disruption index (DI)	
1	0.4801	0.3793	0.2119	0.0000	
2	0.3461	0.3012	0.0943	0.0614	
3	1.1782	0.8012	0.7928	0.6429	
4	0.4809	0.4332	0.1002	0.1687	
5	1.0022	0.7110	0.6124	0.5000	
6	0.6350	0.4431	0.4036	0.0909	Table VI
7	0.7019	0.5882	0.2392	0.1765	Project management
8	0.3453	0.2910	0.1143	0.0000	index PMI and disruption
9	0.3964	0.3312	0.1370	0.0588	index D

to the increased number of abnormal days (18 days were abnormal out of 28 total actual working days and thus producing the lowest value of disruption index which is equal to 18/28 = 0.64).

The increased number of abnormal days, in a certain project, reflects poor project management and poor labor productivity. Higher values of both DI and PMI are indications of sub-standard labor performance and poor management. As the PMI continues to increase in value, one would expect more abnormal days or disruption, and accordingly the DI also increases. When the DI exceeds the value of 0.5, the PMI increases at a higher rate, as shown in Figure 2, which demonstrates the exponential correlation ($R^2 = 0.6336$) between the two indices.

Conclusion

Daily labor productivity for nine projects in different locations in the Gaza Strip were investigated in order to determine the value of the baseline productivity in each one. Also other project benchmarks such as disruption index (DI), performance ration (PR) and project management index (PMI) have been calculated for all nine projects. The DI and PMI indices were found to have a correlated relationship. The higher values of both indices indicate poor labor productivity.

Checking the DI values in the nine projects reveals that the higher DI the more likely the project experienced abnormal work days (poor productivity). DI values for four projects were found to be very small (i.e. less than 0.1) indicating that four out of nine targeted projects performed reasonably well. Also, the PMI values of in these four projects were found to be less than 0.4, therefore both of DI and PMI could be considered as guiding indicators of project labor performance.

It was also noticed that two out of the nine targeted projects were performing badly as their DI values were higher than 0.4. The PR and PMI values for these two particular projects were greater than 2.0 and 0.5, respectively.

The management of each contracting company should maintain its own record which describing the baseline productivity in different previous projects with similar conditions. Such records help estimating labor productivity in future projects. Also the project managers should be capable to interpret the reasons behind the differences in



IIPPM

56,4

366



the productivity values in different projects. At the site management level, a daily progress report must include the required information necessary to obtain the baseline productivity. It is strongly recommended to develop a benchmarking standard for each construction firm in Palestine, which may lead to an improvement in the national construction productivity.

Benchmarking labor productivity

References

- Abdel-Hamid, M., Abd Elshakour, H. and Abdel-Razek, R. (2004), "Improving construction labor productivity in Egypt using benchmarking", Banha Higher Institute of Technology, Banha.
- Abdel-Razek, R.H. (1992), "Measuring and improving construction productivity using work measurement techniques", *Proceedings of the International Colloquium on Structural Engineering, Cairo*, pp. 445-546.
- Abdel-Razek, R.H. (2004), "Productivity of Egyptian temporary labor in excavation work", Journal of Egyptian Society of Engineers, Vol. 43 No. 3, pp. 3-8.
- Abdel-Razek, R.H. and Hosny, A. (1990), "Improving bricklayers' productivity", Proceedings of the Frst Alexandria Conference on Structural and Geotechnical Engineering, Egypt, pp. 857-67.
- Abdel-Razek, R.H. and McCaffer, R. (1990), "Evaluating variability in labor productivity", Proceedings of the 3rd International Symposium, International Project Management Association, Egypt, pp. 527-50.
- Adrian, J.J. (1987), Construction Productivity Improvement, Elsevier Science Publication Co., New York, NY.
- Adrian, J.J. and Boyer, L.T. (1976), "Modeling method productivity", Journal of Construction Division, Vol. 102 No. 1, pp. 157-68.
- Ballard, G. and Howell, G. (1998), "Shielding production: essential step in production control", Journal of Construction Management & Engineering, Vol. 124 No. 1, pp. 11-17.
- El-Mashaleh, M., O'Brien, W.J. and London, K. (2001), "Envelopment methodology to measure and compare subcontractor productivity at the firm level", *Proceedings of the 9th Annual Conference of the International Group for Lean Construction, National University of Singapore, Singapore, 6-8 August.*
- Ganesan, S. (1984), "Construction productivity", Habitat International, Vol. 8 Nos 3/4, pp. 29-42.
- Hosny, A. and Abdel-Razek, R.H. (1992), "Improving productivity of tiling operations: a case study", Proceedings of the International Colloquium on Structural Engineering, Ain Shams University, Cairo, pp. 397-408.
- Mohamed, S. (1996), "Benchmarking and improving construction productivity", *International Journal of Benchmarking for Quality and Technology*, Vol. 3 No. 3, pp. 50-8.
- Thomas, R.H. (1994), "Effects of scheduled overtime on labor productivity", Journal of Construction Engineering and Management, Vol. 118 No. 1, pp. 60-7.
- Thomas, R.H. and Napolitan, C.L. (1995), "Quantitative effects of construction changes on labor productivity", *Journal of Construction Engineering and Management*, Vol. 121 No. 3, pp. 290-6.
- Thomas, R.H. and Sanders, S.R. (1991), "Factors affecting masonary-labor productivity", Journal of Construction Engineering and Management, Vol. 117 No. 4, pp. 626-44.
- Thomas, R.H. and Zavrski, I. (1999a), "Construction baseline productivity", Journal of Construction Engineering and Management, Vol. 125 No. 5, pp. 293-303.
- Thomas, R.H. and Zavrski, I. (1999b), *Theoretical Model for International Benchmarking Labor Productivity*, Technical Report No. 9913, Pennsylvania Transportation Institute, University Park, PA.

IJPPM	
56,4	

368

Thomas, R.H., Horman, M.J., Lemes de Souza, U.E and Zavriski, I. (Eds) (2002), Benchmarking of Labor-intensive Construction Activities: Lean Construction and Fundamental Principles of Working Management, CIB publication no. 276, avalable at: http://cibworld.xs4all.nl/dl/ib/ 0202/Pub276.pdf

Further reading

- Halligan, D.W. (1994), "Action response model and loss productivity in construction", Journal of Construction Engineering and Management, Vol. 120 No. 1, pp. 47-62.
- Olomolaiye, P.O. (1998), *Construction Productivity Management*, Addison Wesley Longman, London.
- Osman, I. and Abdel-Razek, R.H. (1996), "Measuring for competitiveness: the role of benchmarking", Proceedings of the Cairo First International Conference on Concrete Structure, Cairo University, Vol. 1, pp. 5-12.

About the authors

Adnan Enshassi is a Professor of Construction Engineering and Management in the Civil Engineering Department at IUG, with over 20 years of research, teaching, and consulting experience in various construction project management disciplines. He was a visiting Professor at Clemson University (USA), Bremen University, Stuttgart Technical University, Berlin Technical University, and Muenchen Technical University (Germany), Graz University (Austria) and Liverpool University (UK). He has developed and conducted many training programs in Construction Project Management for Palestinian Engineers with local institutions and International Organizations like the World Bank, UNDP, UNRWA, WHO, UNESCO and ILO. He is a Member/Fellow of a number of international professional institutions in the USA and UK. He is listed in Marquis *Who's Who in Science and Engineering*. Professor Enshassi has published over 80 research papers in refereed international journals and conferences. He has been awarded the University scientific research prize for Science and Engineering in 2005. He Speaks Arabic, English and German. Adnan Enshassi is the corresponding author and can be contacted at: enshassi@iugaza.edu.ps

Sherif Mohamed is Professor and Director of the Centre for Infrastructure Engineering and Management at Griffith University, Queensland, Australia. His research interests lie in the area of project and construction management. More specifically he focuses on the development of theoretical knowledge and operational tools needed for effective process management. He has authored and co-authored over 100 refereed journal and conference publications in the last ten years.

Peter Mayer, holds a civil engineering diploma from Technische Universitaet Munich/Germany (TUM), an MBA from INSEAD/France and a PhD from Innsbruck University, Austria. After 20 years of practice, first as partner in a Management Consulting firm, then as Managing Partner in a Project Management Consulting firm, he joined academia in 1992. At present, he is Professor at the TUM, served there as vice dean between 2003 and 2006, and, since 1987, he is a public appointed expert for pricing, billing, and project management in construction. He has written various papers in German and international project management journals and a German book on project management. He is a member of the German IPMA branch and several other professional commissions and committees.

Karem Abed is a Master Degree candidate at the Faculty of Engineering (IUG). He is currently working as a project manager in the UNDP. He worked in the United Arab Emirates as an acting project manager in multi-millions projects.

To purchase reprints of this article please e-mail: **reprints@emeraldinsight.com** Or visit our web site for further details: **www.emeraldinsight.com/reprints**

This article has been cited by:

- Shamil George Naoum London South Bank University, London, UK. 2016. Factors influencing labor productivity on construction sites. *International Journal of Productivity and Performance Management* 65:3, 401-421. [Abstract] [Full Text] [PDF]
- Abdulaziz M. Jarkas, R. Malcolm W. Horner. 2015. Creating a baseline for labour productivity of reinforced concrete building construction in Kuwait. *Construction Management and Economics* 33:8, 625-639. [CrossRef]
- 3. Parviz Ghoddousi School of Civil Engineering, Iran University of Science and Technology, Tehran, Iran Omid Poorafshar School of Civil Engineering, Iran University of Science and Technology, Tehran, Iran Nicholas Chileshe School of Natural and Built Environments, University of South Australia, Adelaide, Australia M. Reza Hosseini School of Natural and Built Environments, University of South Australia, Adelaide, Adelaide, Australia . 2015. Labour productivity in Iranian construction projects. *International Journal of Productivity and Performance Management* 64:6, 811-830. [Abstract] [Full Text] [PDF]
- 4. Shamil NaoumProductivity in Construction Projects 93-106. [CrossRef]
- 5. Parviz Ghoddousi and Department of Civil Engineering, Iran University of Science and Technology, Tehran, Iran Behzad T. Alizadeh Department of Civil Engineering, Iran University of Science and Technology, Tehran, Iran M. Reza Hosseini School of Natural and Built Environments, University of South Australia, Adelaide, Australia Nicholas Chileshe School of Natural and Built Environments, University of South Australia, Adelaide, Australia . 2014. Implementing the international benchmarking labour productivity theoretical model. *Benchmarking: An International Journal* 21:6, 1041-1061. [Abstract] [Full Text] [PDF]
- Craig Langston Institute of Sustainable Development and Architecture, Bond University, Gold Coast, Australia . 2014. Construction efficiency: a tale of two developed countries. *Engineering, Construction and Architectural Management* 21:3, 320-335. [Abstract] [Full Text] [PDF]
- 7. André de WaalMaastricht School of Management, Maastricht, The Netherlands Suhail SultanPalestine Polytechnic University, Hebron, Palestine. 2012. Applicability of the high performance organization framework in the Middle East. *Education, Business and Society: Contemporary Middle Eastern Issues* 5:3, 213-223. [Abstract] [Full Text] [PDF] [Supplemental Material]
- 8. Competencies That Drive the Company 173-222. [CrossRef]
- Jong-Soo Choi, Young-Jun Choi, Seong-Tae Chae, Sung-Won Yoo. 2009. Assessment of Project Cost Reduction Potential Adopting Cases-Synthetic Approach - Focused on the Apartment Building Construction Project -. *Journal of the Korea Institute of Building Construction* 9:5, 135-144. [CrossRef]